

ATV QUAD 4T

SAE 10W/40 JASO MA2

High-quality synthetic motor oil for four-stroke ATVs/Quads

Description

MOTOREX ATV QUAD 4T is a modern, synthetic blend motor oil for ATVs/Quads. This oil offers a good level of shear stability and a short lubrication rise time, even at low temperatures. JASO MA2 approval guarantees the fault-free functioning of wet multi-disc clutches.

Advantages

- outstanding wear protection
- excellent cold-starting properties
- high shear stability

Field of application

MOTOREX ATV QUAD 4T SAE 10W/40 is formulated for tough conditions in the four-stroke engines of ATVs (all-terrain vehicles) and Quads. Meets the requirements of the manufacturer's specifications.

Specifications

JASO MA2; API SL; API SJ; API SH; API SG



JASO T 903 : 2016
PERFORMANCE IS GUARANTEED by
BUCHER AG

Technical data

Properties	Unit	Test according to	Values
Colour			yellow-brown
Density at 20 °C	g/cm ³	ASTM D4052	0.858
Viscosity at 40 °C		DIN 51562-1	85.8
Viscosity at 100 °C		DIN 51562-1	13.2
Viscosity index		DIN ISO 2909	154
Viscosity according to HTHS at 150 °C		CEC-L-36 A-97	≥3.5
Pourpoint		ASTM D5950	-36
Flash point C.O.C.		DIN EN ISO 2592	≥200
CCS at		ASTM D 5293	-25 / 4935
Sulphate residue content		DIN EN ISO 6245	0.8
Phosphor			0.09
Sulfur			0.23
NOACK		CEC L-40-A-93	12
TBN		DIN ISO 3771	5.7

European waste code: 13 02 05 / Water hazard class: 1

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.

