



PRISMA ZX

SAE 75W/80

Synthetic Performance oil for manual gearboxes and final drives. API GL-4+5.

Description

MOTOREX GEAR OIL PRISMA ZX SAE 75W/80 is a versatile synthetic high-lubricity oil. It provides optimum lubrication over a wide temperature range, both in synchronised and non-synchronised manual gearboxes and final drives, even under high loads.

Field of application

MOTOREX GEAR OIL PRISMA ZX SAE 75W/80 has been especially developed for front-wheel-drive vehicles. The formulation guarantees perfect synchronisation in manual gearboxes and reliable lubrication of the integrated differential. The low viscosity guarantees excellent cold starting.

MOTOREX PRISMA ZX SAE 75W/80 is excellent for vehicles such as VW/AUDI, RENAULT, PEUGEOT and CITROËN.

Please check with manufacturers' specifications.

Advantages

- Optimum wear protection
- Excellent oxidation and shear stability
- Excellent viscosity temperature characteristics
- Good anti-foaming behaviour
- Very low pourpoint

Specifications

API GL-4 + 5
Safety + Performance: ZF TE-ML 08

Technical data

Properties	Unit	Test according to	Values
Viscosity class		SAE J 306	75W/80
Colour		DIN ISO 2049	yellow
Density at 20 °C	g/ml	ASTM D 4052	0.861
Viscosity at 40 °C	mm ² /s	DIN 51562-1	49.6
Viscosity at 100 °C	mm ² /s	DIN 51562-1	9.4
Viscosity index		DIN ISO 2909	175
Brookfield -40 °C	mPa·s	ASTM D 2983	32500
Pourpoint	°C	ASTM D 5950	-45
Flash point	°C	DIN EN ISO 2592	> 220

Water hazard class: WGK 1

Disposal code: EWC 130 205

The above information is subject to change without prior notice, although it is in accordance with current standards. Performance characteristics indicated are based on usual tolerances which occur during measuring and production using the latest technology. A safety data sheet is available for the product described.

