

SCOOTER GEAR OIL ZX (80W/90)

SEMI SYNTHETIC

API GL 4+5

Description

Semi-synthetic scooter gear oil. Developed especially for a variable transmission drive in scooters. Optimum friction coefficient.

Advantages

- Above average load bearing capability
- Extremely smooth gear-changing over the full temperature range and the entire period of use
- Excellent protection against wear
- Good viscosity and temperature characteristics
- Excellent oxidation and ageing stability

Quantity: 130ml / 4.39fl.oz



Technical data

Properties	Unit	Test according to	Values
Viscosity class		SAE J 306	80W/90
Colour		DIN ISO 2049	brown
Density at 20 °C	g/ml	ASTM D 4052	0.895
Viscosity at 40 °C	mm ² /s	DIN 51562-1	138.8
Viscosity at 100 °C	mm ² /s	DIN 51562-1	14.5
Brookfield -26 °C	mPa·s	DIN 51398	122'670
Viscosity index		DIN ISO 2909	103
Pourpoint	°C	ASTM D 5950	-30
Flash point	°C	DIN EN ISO 2592	>220

Water hazard class: WGK 1

Disposal code: EWC 130 205

The above information is subject to change without prior notice, although it is in accordance with current standards. Performance characteristics indicated are based on usual tolerances which occur during measuring and production using the latest technology. A safety data sheet is available for the product described.